



螺丝孔及螺丝尺寸 STUD SIZE	
mm - inch	mm - inch
3.2 - #4	6.4 - 1/4"
3.7 - #6	8.4 - 5/16"
4.3 - #8	10.5 - 3/8"
5.3 - #10	13.0 - 1/2"

绝缘端子基本颜色	
红 RED:	1.25 mm ² = AWG 22-16
蓝 BLUE:	2.0 mm ² = AWG 16-14
黑 BLACK:	3.5 mm ² = AWG 14-12
黄 YELLOW:	5.5 mm ² = AWG 12-10
●特殊颜色，欢迎洽询	

型号	产品名称	英文-产品名称
R	R型端子	Ring Terminal
Y	Y型端子	Y Terminal
H	钩型端子	Hook Terminal
LY	折角Y型端子	Flanged Spade Terminal
RF	R型绝缘端子	Insulated Ring Terminal
YF	Y型绝缘端子	Insulated Y Terminal
ERF	R型易进式绝缘端子	Insulated Ring Terminal Easy Entry
EYF	Y型易进式绝缘端子	Insulated Y Terminal Easy Entry
HF	绝缘钩型端子	Insulated Hook Terminal
LXF	折角Y型绝缘端子	Flanged Spade Insulated Terminal
B	长铜管	Butt Splice
P	短铜管	Parallel Splice
PIN-AF	针型端子	Pin Insulated Terminals
PIN	针型裸端子	Pin Terminals
EPIN-AF	针型易进式端子	Pin Insulated Terminals Easy Entry
BF	中接端子	Butt Splice Insulated
BHS	防水热收缩中接端子	Butt Splice (Water Proof & Heat Shrinkable)
BN	尼龙中接端子	Nylon Insulated Butt Splice
LV-B	公母插(公)	Male Lug
LV-A	公母插(母)	Female Lug
1.25-7A 2-7A 5.5-7A	公母插(母)	Non Insulated Female Lug
PV-A	绝缘公母插(母)	Insulated Female Lug
MF-A	钩型公母插	Piggy Back Disconnects
PN-A	尼龙绝缘公母插(母)	Nylon Insulated Female Lug
PN-B	尼龙绝缘公母插(公)	Nylon Insulated Male Lug
ELV-B	易进式公母插(公)	Male Lug Easy Entry
ELV-A	易进式公母插(母)	Female Lug Easy Entry
CLV-A	公母插保护套	Female Lug Cover
F-B	子弹型(公)	Insulated Bullet
F-A	子弹型(母)	Fully Receptacle
FNH-B	尼龙绝缘子弹型(公)加铜套	Nylon Insulated Bullet
FNH-A	尼龙绝缘子弹型(母)加铜套	Nylon Fully Receptacle
FL-A	旗型裸端子	Flag Female Disconnects
VTL	透明旗型绝缘套	Vinyl Flag Sleeve
FLN-A	尼龙绝缘旗型端子	Nylon Insulated Flag Female Disconnects
BD	扁平端子	Blade Terminal
BD-F	扁平绝缘端子	Blade Insulated Terminal
LB	折角扁平端子	Lipped Blade Terminal
LB-F	折角扁平绝缘端子	Lipped Blade Insulated Terminal
VT	透明绝缘套	Vinyl Sleeve
C	铜管端子	Cable Lugs
CL	高压长型端子(单孔式)	Cable Lugs-High Voltage
CL-2D	高压长型端子(双孔式)	Cable Lugs-High Voltage
BL	高压长铜管	Cable Lugs-High Voltage
TC CTC TP	C型铜压接管	C Type Copper Compression Connectors